

NAME	Michal Abramowicz	TEMP	°C	ENGINE	GXR-15	MUFFLER	standard/kit
DATE	2008-09-23	HUMIDITY	%	HEAD CLEARANCE	mm	FUEL TYPE	16% tornado
TRACK	Klodzko	TRACTION	%	PLUG No.	standard	RADIO	3PK spektrum pro
EVENT	V GP Klodzko	CITY	Klodzko	Poland	SHOCK OIL		300 350 400 450 500 550 600

SHOCK TYPE	N / VZ075	
DIAPHRAGM	N	
SHOCK PISTON	N	
SPRING	N AE Copper Spring 25 lbs	
SPRING ADJUSTER	3 mm	
SHOCK POSITION	1 2 3	
CASTER ANGLE	mm	
CAMBER ANGLE OG/1G	L	0 0.5 1 1.5 2 2.5 3
	R	0 0.5 1 1.5 2 2.5 3
TOE ANGLE	0	
FRONT WIDTH	198 mm	
UP STOP	mm	
DOWN STOP	mm	
SERVO SAVER	9	10
SERVO ANGLE	%	
UPPER ARM POSITION	<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>	
SHOCK OIL	N	300 350 400 450 500 550 600
SHOCK TYPE	N / VZ075	
DIAPHRAGM	N	
SHOCK PISTON	N	
SPRING	N AE Red Spring 22 lbs	
SPRING ADJUSTER	3 mm	
SHOCK POS	1 2 3 4	
WHEEL SPACER	0mm / 2mm	
UPPER ARM HEIGHT	mm IN/OUT	
CAMBER ANGLE OG/1G	L	0 0.5 1 1.5 2 2.5 3 3.5 4
	R	0 0.5 1 1.5 2 2.5 3 3.5 4
TOE ANGLE	3	
REAR WIDTH	200 mm	
DOWN STOP	mm	
ANTIROLL BAR	N	1.3/1.4
TIRE TYPE & HARDNESS	xceed 30mm 42	
INNER FOAM		
WHEEL TYPE		

SHOCK OIL	N 300 350 400 450 500 550 600	
SHOCK TYPE	N / VZ075	
DIAPHRAGM	N	
SHOCK PISTON	N	
SPRING	N AE Red Spring 22 lbs	
SPRING ADJUSTER	3 mm	
SHOCK POS	1 2 3 4	
WHEEL SPACER	0mm / 2mm	
UPPER ARM HEIGHT	mm IN/OUT	
CAMBER ANGLE OG/1G	L	0 0.5 1 1.5 2 2.5 3 3.5 4
	R	0 0.5 1 1.5 2 2.5 3 3.5 4
TOE ANGLE	3	
REAR WIDTH	200 mm	
DOWN STOP	mm	
ANTIROLL BAR	N	1.3/1.4
TIRE TYPE & HARDNESS	xceed 30mm 42	
INNER FOAM		
WHEEL TYPE		

SHOCK OIL	N 300 350 400 450 500 550 600	
SHOCK TYPE	N / VZ075	
DIAPHRAGM	N	
SHOCK PISTON	N	
SPRING	N AE Red Spring 22 lbs	
SPRING ADJUSTER	3 mm	
SHOCK POS	1 2 3 4	
WHEEL SPACER	0mm / 2mm	
UPPER ARM HEIGHT	mm IN/OUT	
CAMBER ANGLE OG/1G	L	0 0.5 1 1.5 2 2.5 3 3.5 4
	R	0 0.5 1 1.5 2 2.5 3 3.5 4
TOE ANGLE	3	
REAR WIDTH	200 mm	
DOWN STOP	mm	
ANTIROLL BAR	N	1.3/1.4
TIRE TYPE & HARDNESS	xceed 30mm 42	
INNER FOAM		
WHEEL TYPE		

SHOCK OIL	N 300 350 400 450 500 550 600	
SHOCK TYPE	N / VZ075	
DIAPHRAGM	N	
SHOCK PISTON	N	
SPRING	N AE Red Spring 22 lbs	
SPRING ADJUSTER	3 mm	
SHOCK POS	1 2 3 4	
WHEEL SPACER	0mm / 2mm	
UPPER ARM HEIGHT	mm IN/OUT	
CAMBER ANGLE OG/1G	L	0 0.5 1 1.5 2 2.5 3 3.5 4
	R	0 0.5 1 1.5 2 2.5 3 3.5 4
TOE ANGLE	3	
REAR WIDTH	200 mm	
DOWN STOP	mm	
ANTIROLL BAR	N	1.3/1.4
TIRE TYPE & HARDNESS	xceed 30mm 42	
INNER FOAM		
WHEEL TYPE		

GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL					
15	61	8.13	15	60	8.00	15	59	7.87	20	56	5.60	20	55	5.50
16	61	7.63	16	60	7.50	16	59	7.38	21	56	5.33	21	55	5.24
17	61	7.18	17	60	7.06	17	59	6.94	22	56	5.09	22	55	5.00
									23	56	4.87	23	55	4.78

FLYWHEEL	N	PINION GEAR	15 16 17 / 20 21 22 23	CHASSIS HEIGHT	mm
CLUCH SHOE	N / UM210	SPUR GEAR	59 60 61 / 55 56	LOWER ARM POSITION	<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>
CLUTCH SPRING	kit	BRAKE	100 %	BODY	
		REAR DIFF	3000	WING HEIGHT	mm

MEMO

Standard kit kyosho V-one SIII with front diferential and 3racing cvd at front. Drive very nice and easy :-)