

Event: Default setup
 Date: _____
 Track: _____
 City: _____
 Name: Factory Default



Set Up Sheet
 Ver. 0601E



Track conditions
 Size: Open Med. Tight
 Traction: High Med. Low
 Surface: Smooth Med. Bumpy

Front suspension

Track width 199 mm
 Ride height 4 mm
 Camber angle -1.5 °
 Upper arm spacer 2 mm
 Toe angle Out 2 °
 Rebound stop 2 mm
 Bump stop None Use
 Upper arm position 1 mm
 Anti-roll bar +45 degrees
 Upright T0138-B T0138
 Upper arm position _____ mm

Front shock

Piston Stock
 Oil # 600
 Spring Light blue
 Sock position

Front Diff.

One way
 Gear diff. Oil # _____
 Rigid

Steering ackerman

A
 B
 C

Rear suspension

Track width 200 mm
 Ride height 5 mm
 Camber angle -3 °
 Toe angle In 2 °
 Rebound stop 5 mm
 Bump stop None Use
 Lower arm position
 Upright spacer 2 mm
 Anti-roll bar Wire ϕ 2.1
0 mm
 Adjustable (T0162)
 Upright position T0144 T0161

Rear Shock

Piston Stock
 Oil # 600
 Spring Light blue
 Shock position

Rear Diff.

Oil # 10000

Engine Type _____
 Gasket _____ mm Muffler _____
 Plug _____ Fuel _____

Clutch

Clutch shoe Black Gray Yellow
 Centrifugal shoe Lightweight
 Spring Super hard
 Clutch bell clearance 0.4 mm
 Spring adj. Nut position 0.8 mm

Tire <Front> Type _____ <Rear> Type _____
 Dia.(start) L /R Dia.(start) L /R
 Dia.(finish) L /R Dia.(finish) L /R

Brake pad

Black Other

Body Type _____
 Wing _____

Drive ratio

Gear ratio Side pulley
 1st. 17 / 59 24T
 2nd. 23 / 53 25T

Result
 Race time / Lap _____
 Best lap (1Lap) _____

Comments:

