

# SETUP SHEET




## TRACK CONDITIONS

Surface:  Smooth  Med.  Bumpy  
 Size:  Open  Med.  Tight  
 Traction:  High  Med.  Low

Track Temp/Air Temp: \_\_\_\_\_ / 25 °

Note: \_\_\_\_\_

## FRONT SUSPENSION



Front Width: 199 mm

Anti-Roll Bar: 90 °

Diff. Fluid: \_\_\_\_\_ wt

One Way

Solid Axle

Toe Angle: 0.5 °

Front Camber: L 3.4 ° R 3.4 °

Front Ride Height: 5 mm

Front Droop: 1 mm

Caster: 2 mm

### ► SHOCK

Shock Length: 64 mm

Thread Length: \_\_\_\_\_ mm

Oil: 35 wt

Piston: 1.2

Spring: 1.5 mm





### ► TIRE

Front Tire: GRP


Shore: L 40 ° R 40 °

Diameter(Start): L/R 61 / 61 mm

Diameter(Finish): L/R \_\_\_ / \_\_\_ mm



## REAR SUSPENSION



Rear Width: 199 mm

Anti-Roll Bar: \_\_\_\_\_ °

Diff. Fluid: 10000 wt

Solid Axle

Toe Angle: 3 °

Rear Camber: L 6 ° R 6 °

Rear Ride Height: 7 mm

Rear Droop: 3 mm

### ► SHOCK

Shock Length: 64 mm

Thread Length: \_\_\_\_\_ mm

Oil: 35 wt

Piston: 1.2

Spring: 1.4 mm



### ► TIRE

Front Tire: GRP


Shore: L 40 ° R 40 °

Diameter(Start): L/R 63 / 63 mm

Diameter(Finish): L/R \_\_\_ / \_\_\_ mm



## Pulley




Front Side Pulley: \_\_\_\_\_ T

Rear Side Pulley: \_\_\_\_\_ T

Brake Pulley: \_\_\_\_\_ T

## ENGINE



Gear Ratio: 1st 18 T / 52 T

2nd 24 T / 46 T

Clutch Set Type:

3 Shoe  Push Type

Clutch Spring: 1.7 mm

Clutch weight: \_\_\_\_\_

Clutch Shoe: \_\_\_\_\_

Engine: LRP SPEC 4

Plug: Novarosi 7

Fuel: Tornado 16


Manifold: LRP

Pipe: LRP

Pipe Length: \_\_\_\_\_ mm

Note: To big gear!

## Body



Body: Dodge Stratus 3

Radio: Sanwa M11

ST. Servo: Kopropo

TH. Servo: Kopropo

## COMMENTS

Race Time / Lap: \_\_\_\_\_

Best Lap Time: \_\_\_\_\_

Position: 2

Notes: Qua first position!